

How To Make A Thesis Following The Guideline With More Text To Have Two Lines



by

A Good Name

Submitted for the degree of

Doctor of Philosophy

SOME WEIRD INSTITUTE NO ONE EVER HEARD ABOUT

SCHOOL OF LATEX AND WRITING

HERIOT-WATT UNIVERSITY

September 2042

Abstract

In accordance with the Academic Regulations the thesis must contain an abstract preferably not exceeding 200 words, bound in to precede the thesis. The abstract should appear on its own, on a single page. The format should be the same as that of the main text. The abstract should provide a synopsis of the thesis and shall state clearly the nature and scope of the research undertaken and of the contribution made to the knowledge of the subject treated. There should be a brief statement of the method of investigation where appropriate, an outline of the major divisions or principal arguments of the work and a summary of any conclusions reached. The abstract must follow the Title Page.

Dedication

If a dedication is included then it should be immediately after the Abstract page.

I don't what it is actually.

Acknowledgements

I wanna thanks all coffee and tea manufacturers and sellers that made the completion of this work possible.

Part I

Chapters

Chapter 1

Introduction

Stellites are a cobalt-base superalloy used in aggressive service environments due to retention of strength, wear resistance, and oxidation resistance at high temperature [4].

Originating in 1907 with Elwood Haynes's development of alloys like Stellite 6, Stellites quickly found use in orthopedic implants, machine tools, and nuclear components, and new variations on the original CoCrWC and CoCrMoC alloys are spreading to new sectors like oil & gas and chemical processing [15, 4].

Stellites generally contain 25-33 wt Cr, 4-18 W/Mo, 0.1-3.3 wt C, and optional trace elements of Fe, Ni, Si, P, S, B, Ln, Mn, as seen in Table 1 [1, 5, 6, 7, 9, 10, 11, 16, 17, 26]. The microstructure of Stellite alloys consists of a CoCr(W,Mo) matrix with solid solution strengthening, with hard carbide phases, usually with Cr (e.g., M_7C_3 , $M_{23}C_6$), and W/Mo (e.g. MC , M_6C); the proportion and type of carbides depend on carbon content and the relative amounts of carbon with carbide formers (Cr, W, Mo), as well as processing routes. In addition to the solid solution toughness and carbide hardness, the stress-induced FCC to HCP phase transformation of the Co-based solid solution further increases wear resistance through work hardening.

Alloy	Co	Cr	W	Mo	C	Fe	Ni	Si	P	S	B	Ln	Mn	Ref	Process Type	Observation
Stellite 1	47.7	30	13	0.5	2.5	3	1.5	1.3					0.5	[9]	Nominal composition	
	48.6	33	12.5	0	2.5	1	1	1.3					0.1	[5]		
	46.84	31.7	12.7	0.29	2.47	2.3	2.38	1.06					0.26	[1]	HIPed ^a	ICP-OES ^b
Stellite 3	50.5	33	14		2.5									[7]		
	49.24	29.57	12.07	0.67	2.52	2.32	1.07	1.79					0.75	[17]	HIPed ^a	ICP-OES ^b
Stellite 4	45.43	30	14	1	0.57	3	3	2					1	[9]	Nominal composition	
	51.5	30	14		1	1	2	0.5						[26]		
	51.9	33	14		1.1									[7]		
	49.41	31	14	0.12	0.67	2.16	1.82	1.04					0.26	[1]	HIPed ^a	ICP-OES ^b
	50.2	29.8	14.4	0	0.7	1.9	1.9	0.8					0.3	[6]	HIPed ^a	
Stellite 6	51.5	28.5	4.5	1.5	1	5	3	2			1		2	[9]	Nominal composition	
	63.81	27.08	5.01		0.96	0.73	0.87	1.47					0.07	[17]	HIPed ^a	ICP-OES ^b
	60.3	29	4.5		1.2	2	2	1						[26]		
	61.7	27.5	4.5	0.5	1.15	1.5	1.5	1.15					0.5	[7]		
	58.46	29.5	4.6	0.22	1.09	2.09	2.45	1.32					0.27	[1]	HIPed ^a	ICP-OES ^b
	58.04	30.59	4.72		1.24	2.03	1.87	0.80	0.01	0.01				[11]	PTAW ^e	OES
	55.95	27.85	3.29		0.87	6.24	3.63	1.23	0.01	0.01			0.45	[11]	GTAW ^d	OES
	52.40	30.37	3.57		0.96	6.46	3.93	1.70	0.01	0.01			0.3	[11]	SMAW ^c	OES

	60.3		31.10	4.70	0.30	1.10	1.70	1.50	1.30	0.00	0.3	[16]	LP-DED	ICP-AES & GDMS
	60.6	27.7	5	0	1.2	1.9	2	1.3			0.3	[6]	HIPed ^a	
Stellite 12	53.6	30	8.3		1.4	3	1.5	0.7			1.5	[9]	Nominal composition	
	55.22	29.65	8.15	0.2	1.49	2.07	2.04	0.91			0.27	[1]	HIPed ^a	ICP-OES
Stellite 19	50.94	31.42	10.08	0.79	2.36	1.82	2	0.4		0.09	0.1	[10]		
Stellite 20	41.05	33	17.5		2.45	2.5	2.5				1	[9]	Nominal composition	
	43.19	31.85	16.3	0.27	2.35	2.5	2.28	1			0.26	[1]	HIPed ^a	ICP-OES
Stellite 21	59.493	27		5.5	0.25	3	2.75	1		0.007	1	[9]	Nominal composition	
	60.6	26.9	0	5.7	0.2	1.3	2.7	1.9			0.7	[6]	HIPed ^a	
Stellite 31	57.5	22	7.5		0.5	1.5	10	0.5			0.5	[9]	Nominal composition	
	52.9	25.3	7.8	0	0.5	1.1	11.4	0.6			0.4	[6]	HIPed ^a	
Stellite 190	46.7	27	14	1	3.3	3	3	1			1	[9]	Nominal composition	
	48.72	27.25	14.4	0.2	3.21	2.1	2.81	1			0.31	[1]	HIPed ^a	ICP-OES*

The remarkable ability of Stellite alloys to withstand these specific challenges stems from key metallurgical features. Their corrosion resistance is primarily attributed to a high chromium content, typically 20-30 wt.%, which promotes the formation of a highly stable, tenacious, and self-healing chromium-rich passive oxide film on the material's surface; this film acts as a barrier isolating the underlying alloy from the corrosive environment. Alloying elements such as molybdenum and tungsten can further enhance this passivity, particularly improving resistance to localized corrosion phenomena like pitting and crevice corrosion in aggressive media. Concurrently, their outstanding cavitation resistance is largely derived from the unique behavior of the cobalt-rich matrix, which can undergo a stress-induced crystallographic transformation from a face-centered cubic (fcc) to a hexagonal close-packed (hcp) structure. This transformation, often facilitated by mechanical twinning, effectively absorbs the intense, localized impact energy from collapsing cavitation bubbles and leads to significant work hardening, thereby impeding material detachment and erosion.

1.1 Paragraph 4: Synergistic Challenges in Applications Prone to Corrosion and Cavitation

IGNORE

1.2 Paragraph 5: Research and Development for Enhanced Corrosion and Cavitation Performance

IGNORE

1.3 Paragraph 6: Influence of HIPing

IGNORE

Compared with the case alloys, the HIPed alloys had relatively finer, rounded, and distributed carbides.

1.4 General Background

%cite:@Franc2004265, @Romo201216, @Kumar2024, @Kim200685, @Gao2024, @20221xix, @Usta2023, @Cheng2023, @Zheng2022

Cavitation erosion presents a significant challenge in materials degradation in various industrial sectors, including hydroelectric power, marine propulsion, and nuclear systems, stemming from a complex interaction between fluid dynamics and material response [12, 18]. Hydrodynamically, the phenomenon initiates with the formation and subsequent violent collapse of vapor bubbles within a liquid, triggered by local pressures dropping to the saturated vapor pressure. These implosions generate intense, localized shockwaves and high-speed microjets that repeatedly impact adjacent solid surfaces [13]. From a materials perspective, these impacts induce

high stresses (100-1000 MPa) and high strain rates, surpassing material thresholds and leading to damage accumulation via plastic deformation, work hardening, fatigue crack initiation and propagation, and eventual material detachment. Mitigating this requires materials capable of effectively absorbing or resisting this dynamic loading, often under demanding conditions that may also include corrosion.

Stellite alloys, cobalt-chromium formulations that contain carbon, tungsten and/or molybdenum, represent a critical class of materials renowned for their wear resistance in such harsh environments [19]. Their performance stems from a composite-like microstructure combining a strong cobalt-rich matrix, strengthened by solid solutions of Cr and W/Mo, with hard carbide precipitates (e.g., M₇C₃, M₂₃C₆) that impede wear and crack propagation [2, 8].

% Martensitic transformation Crucially, the cobalt matrix often possesses a low stacking fault energy, facilitating a strain-induced martensitic transformation from a metastable face-centered cubic γ phase to a hexagonal close-packed ϵ phase under the intense loading of cavitation. This transformation is a primary mechanism for dissipating impact energy and enhancing work hardening, contributing significantly to Stellite's characteristic cavitation resistance [14, 22].

HIPing is a thermo-mechanical material processing technique which involves the simultaneous application of pressure (up to 200 MPa) and temperature (2000 C), which results in casting densification, porosity closure, and metallurgical bonding. [25]

While commonly applied via casting or weld overlays, processing routes like Hot Isostatic Pressing (HIP) offer potential advantages such as microstructure refinement [20] finer microstructures and enhanced fatigue resistance [3, 25].

HIPing of surface coatings results in microstructure refinement, which can yield improved fatigue and fracture resistance.

HIPing leads to carbide refinement, which can yield improved impact toughness [24], and reduce carbide brittleness [25].

Furthermore, HIP facilitates the consolidation of novel 'blended' alloys created from mixed elemental or pre-alloyed powders, providing a pathway to potentially tailor compositions or microstructures for optimized performance. However, despite the prevalence of Stellite alloys and the known influence of processing on microstructure and properties, the specific cavitation erosion behavior of HIP-consolidated Stellites, particularly these blended formulations, remains underexplored in academic literature. Given that erosion mechanisms in Stellites often involve interactions at the carbide-matrix interface [21], understanding how HIP processing and compositional blending affect these interfaces and the matrix's transformative capacity under cavitation, especially when potentially coupled with corrosion, constitutes a critical knowledge gap addressed by this research.

1.5 Stellite 1

Stellite 1 is a high-carbon and high-tungsten alloy, making it suitable for demanding applications that require hardness & toughness to combat sliding & abrasive wear [8]

1.6 Stellites

1.7 Objectives and Scope of the Research Work

1.8 Thesis Outline

1.9 Literature Survey

1.10 Cavitation Tests

Chapter 2

Analytical Investigations

Chapter 3

Experimental Investigations

3.1 Materials and Microstructure

The HIPed alloy was produced via canning the gas-atomized powders at 1200C and 100 MPa pressure for 4h, while the cast alloys were produced via sand casting. % Sieve analysis and description of powders

% Refer to Table of chemical compositions of both cast and HIPed alloys.

The microstructure of the alloys were observed via SEM in BSE mode, and the chemical compositions of the identified phases developed in the alloys were determined via EDS as well as with XRD under Cu K_{α} radiation.

Image analysis was also conducted to ascertain the volume fractions of individual phases.

The Vickers microhardness was measured using a Wilson hardness tester under loads of BLAH. Thirty measurements under each load were conducted on each sample.

Chapter 4

Discussion

4.1 Experimental Test Procedure

4.1.1 Hardness Tests

4.1.2 Cavitation

4.2 Relationships between cavitation erosion resistance and mechanical properties

4.3 Influence of vibratory amplitude

% Insert the whole spiel by that French dude about displacement and pressure (and then ruin it) The pressure of the solution depends on the amplitude of the vibratory tip attached to the ultrasonic device. Under simple assumptions, kinetic energy of cavitation is proportional to the square of the amplitude and maximum hammer pressure is proportional to A.

$$x = A \sin(2\pi ft) \quad (4.1)$$

$$v = \frac{dx}{dt} = 2\pi f A \sin(2\pi ft) \quad (4.2)$$

$$v_{max} = 2\pi f A \quad (4.3)$$

$$v_{mean} = \frac{1}{\pi} \int_0^\pi A \sin(2\pi ft) = 4fA \quad (4.4)$$

$$(4.5)$$

However, several researchers have found that erosion rates are not proportional to the second power of amplitude, but instead a smaller number. Thiruvengadam [23] and Hobbs find that erosion rates are proportional to the 1.8 and 1.5 power of peak-to-peak amplitude. Tomlinson et al find that erosion rate is linearly proportional to peak-to-peak amplitude in copper [3]. Maximum erosion rate is approximately proportional to the 1.5 power of p-p amplitude [4]. The propagation of ultrasonic waves may result in thermal energy absorption or into chemical energy, resulting in reduced power. For the purposes of converting data from studies that do not use an amplitude of 50um, a exponent factor of 1.5 has been applied.